


Product Specification

XLPE INSULATED, PVC SHEATHED CABLES (NON-ARMOURED)



Cu / XLPE / PVC - 4 Cores

Nominal cross-sectional area	Construction, number / wire diameter	Thickness of insulation	Thickness of sheath	Approx. overall diameter	Approx. net weight
sq.mm	No./mm	mm	mm	mm	kg/km
IEC 60502-1 / BS 5467 / MS 2106 600 / 1000 V					
1.5	7/0.53	0.7	1.8	10.9	173
2.5	7/0.67	0.7	1.8	11.8	225
4	7/0.85	0.7	1.8	13.0	302
6	7/1.04	0.7	1.8	15.3	400
10	7/1.35	0.7	1.8	17.2	595
16	7/1.70	0.7	1.8	19.9	825
25	7/2.14	0.9	1.8	23.7	1260
35	19/1.53	0.9	1.8	24.4	1650
50	19/1.78	1.0	1.9	28.0	2180
70	19/2.14	1.1	2.0	32.2	3080
95	19/2.52	1.1	2.1	35.5	4170
120	37/2.03	1.2	2.3	39.6	5260
150	37/2.25	1.4	2.4	44.4	6390
185	37/2.52	1.6	2.6	47.9	8000
240	61/2.25	1.7	2.8	55.6	10500
300	61/2.52	1.8	3.0	61.9	13050
400	61/2.85	2.0	3.3	68.7	16100