


XLPE INSULATED, PVC SHEATHED ARMOURED CABLES



Cu / XLPE / Swa / PVC - 3 Cores

Nominal cross-sectional area	Number and diameter of wire	Thickness of Insulation	Diameter of steel wire	Thickness of sheath	Approx. overall diameter	Approx. net weight
sq.mm	No./mm	mm	mm	mm	mm	kg/km
IEC 60502-1 / BS 5467 / MS 2107 600 / 1000 V						
1.5	7/0.53	0.7	0.9	1.8	14.1	383
2.5	7/0.67	0.7	0.9	1.8	15.0	450
4	7/0.85	0.7	0.9	1.8	16.1	532
6	7/1.04	0.7	0.9	1.8	17.8	640
10	7/1.35	0.7	1.25	1.8	20.3	830
16	7/1.70	0.7	1.25	1.8	22.6	1050
25	7/2.14	0.9	1.6	1.8	26.7	1650
35	19/1.53	0.9	1.6	1.8	26.0	2000
50	19/1.78	1.0	1.6	1.9	29.2	2500
70	19/2.14	1.1	2.0	2.0	34.2	3540
95	19/2.52	1.1	2.0	2.2	37.6	4550
120	37/2.03	1.2	2.0	2.3	42.9	5500
150	37/2.25	1.4	2.5	2.5	49.1	6950
185	37/2.52	1.6	2.5	2.6	50.6	8100
240	61/2.25	1.7	2.5	2.8	58.0	10480
300	61/2.52	1.8	2.5	3.0	61.7	12600
400	61/2.85	2.0	2.5	3.2	66.5	16300