


XLPE INSULATED, PVC SHEATHED ARMOURED CABLES



Cu / XLPE / Swa / PVC - 4 Cores

Nominal cross-sectional area	Number and diameter of wire	Thickness of Insulation	Diameter of steel wire	Thickness of sheath	Approx. overall diameter	Approx. net weight
sq.mm	No./mm	mm	mm	mm	mm	kg/km
IEC 60502-1 / BS 5467 / MS 2107 600 / 1000 V						
1.5	7/0.53	0.7	0.9	1.8	14.7	431
2.5	7/0.67	0.7	0.9	1.8	15.6	510
4	7/0.85	0.7	0.9	1.8	16.8	610
6	7/1.04	0.7	1.25	1.8	19.8	740
10	7/1.35	0.7	1.25	1.8	21.8	990
16	7/1.70	0.7	1.6	1.8	25.1	1530
25	7/2.14	0.9	1.6	1.8	28.9	2100
35	19/1.53	0.9	1.6	1.9	29.8	2500
50	19/1.78	1.0	1.6	2.0	33.4	3400
70	19/2.14	1.1	2.0	2.2	39.0	4550
95	19/2.52	1.1	2.0	2.3	42.3	5800
120	37/2.03	1.2	2.5	2.5	47.8	7250
150	37/2.25	1.4	2.5	2.6	52.6	8950
185	37/2.52	1.6	2.5	2.8	56.1	10850
240	61/2.25	1.7	2.5	3.0	64.2	13800
300	61/2.52	1.8	2.5	3.2	70.5	16600
400	61/2.85	2.0	3.15	3.5	79.0	21800